



(SECTIONAL VIEW)

Notes:

- CERTIFICATION: H0 Lloyd's Register of Shipping, Certificate No. SAS F000315. Blast over-pressure to 0.47 barG.
- MOVEMENT: Multi-leaf construction designed to suit significant movement particularly in the axial direction.
- CLIPPING: Each seal is supplied with fitting instructions, adhesive and stainless steel worm drive clips to suit pipe and sleeve diameters. For diameters of 350mm and above 'double clipping' is required. The clipping length or cuff (B) is 50mm for single clips and 75mm for double clips.
- GENERAL: The bulkhead penetration featured here may also be applied to a deck penetration.

Drawing Title:

FIRETEX BELLOWS TYPE PENETRATION SEAL

Rev	Date	Revision detail	Drn	Chkd	App'd
A	02/06/10	Values updated		M.A.T	J.D.
0	22.11.06	Drawing Created		A.R.	N.R.T
Drawing Number					



**MCL UNITEX LTD**  
 MCL House, Adams Close,  
 Heanor Gate Industrial Park,  
 Heanor, Derbyshire,  
 DE75 7SW  
 United Kingdom  
 Tel: +44 (0)1773 761226  
 Fax: +44 (0)1773 533478  
 Web: www.mclunitex.com

Q05151