



Notes:

- MOVEMENT:** Standard seal construction will accommodate +/-25mm in any plane (except where pipe eccentricity restricts lateral movement).
- CLIPPING:** Each seal is supplied with fitting instructions, adhesive and stainless steel worm drive clips to suit pipe and sleeve diameters. For diameters of 350mm and above 'double clipping' is required. The clipping length or cuff (B) is 30mm for single clips and 70mm for double clips.
- GENERAL:** The deck penetration solution featured here may also be applied to a bulkhead penetration.

Drawing Title:

SPECIAL FIRETEX PIPE PENETRATION SEAL SYSTEM - ECCENTRIC INSTALLATION



MCL UNITEX LTD
 MCL House, Adams Close,
 Heanor Gate Industrial Park,
 Heanor, Derbyshire,
 DE75 7SW
 United Kingdom
 Tel: +44 (0)1773 761226
 Fax: +44 (0)1773 533478
 Web: www.mclunitex.com

Rev	Date	Revision detail	Drn	Chk'd	App'd
B	16/11/10	Cuff sizes altered	M.A.T.	J.D.	N.R.T.
A	02/06/10	Values updated	M.A.T.	J.D.	N.R.T.
0	19/09/05	Drawing Created	J.D.	N.R.T.	I.C.K.
Drawing Number					